APPROVAL SHEET

Wireless Mouse+Keyboard

MODEL NO.: SP-KM202

Article No. : SP-AP-SA-A046 **Issue Date :2012-3-28** **Version : A/0**	**Audited by**

Checked by	**Drafted by**

Spire Corp.

Tel.: +86-755-26801567 Fax: +86-755-26801561

Http://www.spire-corp.com
Http://www.spirepower.com
Http://www.spirecoolers.com

Approval Sheet Revisement Record

Article No: SP-AP-SA-A046

Version	Revised Chapter	Description	Revised Date	Drafted by	Audited by	ECN No.

Contents

1 Features ……4

2 Specification ……5

3 Environmental ……7

4 Pictures ……8

1 Features:

Mouse：

. 2.4G Hz free moving within 10 metres
. Power on /off function
. Receiver storage space and carrying easily
. Rated working current: 3 v, 16 mA
. Low power consumption:2* AAA batteries support
. Plug and play, no driver needed
. Ergonomic design for both right and left handed use
. Compatible with Microsoft Windows 95/98/ME/NT/2000/XP/Vista/Win 7

Keyboard:

. 2.4G Hz free moving within 10 metres.
. Powered by 1*AAA alkaline batteries.
. Ultra-thin keys, quick-witted, loudspeaker mute and easy to operate
. 10 millions times of key life, it's a really durable keyboard
. Lifespan: 10,000,000 times
. Compatible with Microsoft Windows 95/98/ME/NT/2000/XP/Vista/Win 7

Mouse:

- **Color:**black
- **Feature:** Plug & Play with ON/OFF switch and Nano receiver
- **Material:** ABS
- **Tracking Resolution:1000dpi**
- **Interface:**USB 2.0
- **Input:** Voltage:3V
  Current:16mA
  Rated power:0.048W
- **Receiving Distance**: 10 meters
- **System Support:** Microsoft Windows 95/98/ME/NT/2000/XP/Vista/Win 7
- **Keystroke lifetime:** 3,000,000 cycles
- **Dimensions**: 102*56*36mm
- Weight: 84g

2 Specification:

Keyboard:

- **Color:**Black
- **Material:** ABS
- **Interface:**USB 2.0
- **Frequency:**2.4GHz
- **Receiving Distance**:10 Meters
- **Input:** Voltage:1.5V
  Current:16mA
- **Total Key count:** 104 keys
- **System Support:** Microsoft Windows 95/98/ME/NT/2000/XP/Vista/Win 7
- **Keystroke lifetime:** 10,000,000 cycles
- **Dimensions** : 445*137*22mm
- **Weight** : 435g

3 Environmental

3.1 Environmental (Operating)

Temperature: 0℃ to 45℃

Humidity: 10% to 85% Relative Humidity (non condensing)

3.2 Environmental (Non-Operating)

Temperature: -15℃ to 60℃

Humidity: 10% to 85% Relative Humidity (non condensing)

4 Pictures:

Spire Corp.

Spire Coolers Corp.
FL7/8 Building B houhai Blvd
Dongjiaotou Industrial Park Shekou
Nanshan,Shenzhen, China
Tel.: +86-0755-26801567
Fax: +86-0755-26801561
W.: www.spire-corp.com

RoHS Declaration of Conformity

Spire hereby declares under our sole responsibility that the product:

Part number: **SP-KM202**

Description:

1. 2.4G Hz free moving within 10 metres
2. Ergonomic design for both right and left handed use
3. Compatible with Microsoft Windows 95/98/ME/NT/2000/XP/Vista/Win 7

Is tested and approved in compliance with the EUROPEAN COUNCIL ROHS DERECTIVE.

(Restriction of Hazardous Substances) which will restrict the use of certain substances in electrical and electronic products: including lead (Pb), mercury, cadmium, hexavalent chromium, and certain halide-containing flame retardants. The directive applies to all electrical and electronic products, their component parts that are placed on the market after July 1, 2006.

Spire Coolers Corp.
PM Engineering Dept.

Nanshan,Shenzhen